

PAINT COLLECTION FILTERS
EDRIZZI® VARIO
MEDIUM



EDRIZZI®

GENERALS

THE THREE TYPES OF EDRIZZI® VARIO ARE THE RESULT OF SEVERAL YEARS OF DEVELOPMENT AND INTENSIVE EXCHANGE WITH THE PAINTS INDUSTRY AND SUPERSEDE THE EDRIZZI® AUTOMOTIVE SYSTEM USED SO FAR. THE PROCESSING OF FIRE-RETARDANT CORRUGATED CARDBOARD MAKES THE EDRIZZI® VARIO SYSTEM SAFE AND ROBUST IN APPLICATION. THE THREE SOLUTIONS SUPPORT THE CHARACTERISTICS OF DIFFERENT TYPES OF COATING AND ADHESION FOR THE ABSORPTION. EVERY AREA OF APPLICATION OF THE PAINTS INDUSTRY IS COVERED BY THIS DEVELOPMENT. THE EDRIZZI® VARIO MEDIUM OFFERS THE SOLUTION FOR THE MAJORITY OF ALL SURFACE MATERIALS AND HAS BEEN TESTED AND USED SUCCESSFULLY SINCE 2003 IN ALL INDUSTRIES.

CONTAINMENT FRAME	CORRUGATED CARDBOARD
SPACER	CORRUGATED CARDBOARD
ABSORPTION CAPACITY	BIS 100 kg/m²
DEGREE OF SEPARATION	UP TO 97%
NOMINAL VOLUME FLOW RATE	2000-3000 m³/m²h
RECOMMENDED INFLOW SPEED	0,25-2 m/s
INITIAL PRESSURE DIFFERENCE WITH NOMINAL VOLUME FLOW RATE	ED300VF: 68 Pa
	ED500VF: 88 Pa
HUMIDITY RESISTANCE	100 –150 g/m2 in 30 min. according to Coop
REACTION TO FIRE	DIN4102, testing for non-flammability, construction material class B1: fire-retardant
LEGEND OF DIMENSIONS H HEIGHT B BASE T CELL THICKNESS	

Reference drawing: vefim_edrizzi

PRODUCT CODE		PRICE (€)	DIMENSIONS (mm)			TEMPERATURE RESISTANCE	EMPTY WEIGHT (g)
			H	B	T		
ED300VM/S*		a.r.	500	500	300	up to 80°C	1124
ED500VM/S*		a.r.	500	500	500	up to 80°C	1892
ED300VM/M**		a.r.	500	500	300	up to 80°C	1124
ED500VM/M**		a.r.	500	500	500	up to 80°C	1892

* S = the filter is supplied disassembled to save space during transport
** M = the filter is supplied already mounted

- Material normally in stock

Vefim S.r.l. si riserva la facoltà di aggiornare senza alcun preavviso le caratteristiche sopra descritte.
La presente documentazione non può essere riprodotta, trascritta o tradotta (in parte o integralmente) senza autorizzazione scritta di Vefim S.r.l. come previsto ai sensi di legge.



Vefim S.r.l. - Sistemi di Filtrazione
www.vefim.it
Tel. +39 045.820.22.79 - Fax +39 045.827.64.95
Ufficio Vendite Italia: venditeitalia@vefim.it