

SYNTHETIC MEDIA FOR
ODOURS ABSORPTION
SCARBON



SCARBON

GENERALS

SYNTHETIC POLYESTER FIBRE MEDIA (SERIES SCARBON) SOAKED WITH ACTIVE CARBON POWDER. IT IS RECOMMENDED FOR DEODORIZING HOME OR FOR LESS DEMANDING APPLICATIONS. IT CAN BE EASILY INSERTED IN FILTERING CELLS ALSO IN COMBINATION WITH OTHER MEDIA AND PRE-FILTERS PLACED TO PROTECT THE ACTIVE CARBON.

COMPOSITION		100% POLYESTER FIBRE	
MAXIMUM OPERATING TEMPERATURE		150°C	
PACKAGING		POLYETHYLENE BAG	
H L D D1 T HEIGHT LENGTH ROLL DIAMETER CARDBOARD TUBULAR DIAMETER FILTERING MEDIA THICKNESS		D1 T H L	

Reference drawing:
 vefim_rotolo

PRODUCT CODE		PRICE		ACTIVE CARBON	WEIGHT	T	REACTION TO FIRE		PERMEABILITY
		(€)	(%)	SURFACE AREA (m²/m²)	(g/m²)	(mm)	EN 60335-2-31	DIN 53 438-3	OF AIR (l/m²/s)
AO150-5	●	a.r.	24	40000	150	5,5	FH2		1050 (a 25 Pa)
AO220-3	●	a.r.	41	100000	220	3,0	FH2		1250 (a 50 Pa)
AO220-5	●	a.r.	35	85000	220	5,5	FH2	F1	1500 (a 50 Pa)
AO220-10	●	a.r.	32	77000	220	10,0	FH2		1500 (a 25 Pa)
AO360-18	●	a.r.	31	120000	360	18,0	FH2		1400 (a 50 Pa)
AO400-11	●	a.r.	38	170000	400	11,0	FH2		1500 (a 50 Pa)
AO450-8	●	a.r.	44	220000	450	8,0			1000 (a 50 Pa)
AO650-12	●	a.r.	38	270000	650	12,0	FH2		1000 (a 50 Pa)
AO360-8	●	a.r.	23	86000	360	8,0	FH2		950 (a 50 Pa)

• Material normally in stock

DIFFERENT DIMENSIONS OR VERSIONS ARE AVAILABLE ON REQUEST

Vefim S.r.l. reserves the right to update without notice the characteristics described above.
 This document may not be reproduced, transcribed, or translated (in part or in full) without specific written permission by Vefim S.r.l as provided for by law.



Vefim S.r.l. - Sistemi di Filtrazione
www.vefim.it
 Tel. +39 045.820.22.79 - Fax +39 045.827.64.95
 Ufficio Vendite Italia: venditeitalia@vefim.it