

WIRE WOUND FILTER CARTRIDGES CFFV



CFFV

GENERALS

USED IN NOT PARTICULARLY DEMANDING APPLICATIONS, THE WIRE WOUND FILTER CARTRIDGES (SERIES CFFV) ARE FILTER ELEMENTS VERY POPULAR FOR THEIR EASY AVAILABILITY, EASE OF USE AND LOW COST. THE MODELS IN POLYPROPYLENE AND COTTON COMPLY WITH FDA STANDARDS FOR FOOD CONTACT.

AVAILABLE FILTER MATERIALS	POLYPROPYLENE COTTON POLYESTER RAYON NYLON GLASS FIBRE	
FILTER MATERIALS AVAILABLE FOR THE INNER CORE	POLYPROPYLENE AISI 304 STAINLESS STEEL AISI 316 STAINLESS STEEL AISI 317 STAINLESS STEEL	
FILTRATION RATING DEGREE (µm)	1 / 3 / 5 / 10 / 20 / 30 / 50 / 100	
HEIGHT	10" / 20" / 30" / 40" / 50"	
EXTERNAL DIAMETER Ø (mm)	66 / 28	
RECOMMENDED PRESSURE DROP	1,7 bar	
MAXIMUM PRESSURE DROP	5,5 bar	
TYPES OF GASKETS AVAILABLE	NONE SILICONE EPDM BUNA VITON TEFLON POLYFOAM	
TYPES OF GASKETS AVAILABLE	DOE WITHOUT SEALS	
	DOE WITH SEALS	
	SOE -222 WITH BLIND BOTTOM	
	SOE -226 WITH BLIND BOTTOM	
	SOE -222 WITH PUSH ROD	
	SOE -226 WITH PUSH ROD	
	SOE -225 WITH PUSH ROD	

DIFFERENT DIMENSIONS OR VERSIONS ARE AVAILABLE ON REQUEST

Vefim S.r.l. reserves the right to update without notice the characteristics described above.
 This document may not be reproduced, transcribed, or translated (in part or in full) without specific written permission by Vefim S.r.l. as provided for by law.