

# PAINT COLLECTION FILTERS

# EDRIZZI® BNF



# EDRIZZI®

## GENERALS

THE EDRIZZI SPACERS ARE PARTICULARLY SUITABLE TO ABATE OVERSPRAY IN THE PAINT BOOTHS, BUT CAN ALSO BE USED IN SPRAYING GLUE OR THE LIKE. THEY CONSIST OF A CUBE IN WHICH IT WAS CREATED A LABIRINTH THAT FORCES THE AIR TO MAKE DIFFERENT SUDDEN CHANGES OF DIRECTION. BOTH SERIES ARE SUITABLE FOR WATER BASED AND SOLVENT BASED PAINT. SERIES BFH: THE BEST SELLING PRODUCT  
SERIES BNF: SPECIALLY DESIGNED FOR THOSE CASES REQUIRING THE USE OF VERY WET PAINT.

CONTAINMENT FRAME	CORRUGATED CARDBOARD
SPACER	CORRUGATED CARDBOARD
FLOW	2000 m <sup>3</sup> /m <sup>2</sup> h
RECOMMENDED AIR SPEED	0,25-2 m/s
DEGREE OF SEPARATION	UP TO 97%
ACCUMULATION CAPACITY	ED300BNF: up to 40 kg/m <sup>2</sup>
	ED500BNF: up to 80 kg/m <sup>2</sup>
INITIAL PRESSURE DROP	ED300BNF: 70 Pa
	ED500BNF: 80 Pa
LEGEND OF DIMENSIONS	
H	HEIGHT
B	BASE
T	CELL THICKNESS

Reference drawing:

vefim\_edrizzi

PRODUCT CODE	PRICE (€)	DIMENSIONS (mm)			RESISTANCE TO MOISTURE nach Coop	EMPTY WEIGHT (g)
		H	B	T		
ED300BNF/S*	a.r.	500	500	300	100-150g/m <sup>2</sup> in 30 min	1050
ED500BNF/S*	a.r.	500	500	500	100-150g/m <sup>2</sup> in 30 min	1650
ED300BNF/M**	a.r.	500	500	300	100-150g/m <sup>2</sup> in 30 min	1050
ED500BNF/M**	a.r.	500	500	500	100-150g/m <sup>2</sup> in 30 min	1650

\* S = the filter is supplied disassembled to save space during transport

\*\* M = the filter is supplied already mounted

- Material normally in stock

Vefim S.r.l. reserves the right to update without notice the characteristics described above.  
This document may not be reproduced, transcribed, or translated (in part or in full) without specific written permission by Vefim S.r.l. as provided for by law.



Vefim S.r.l. - Sistemi di Filtrazione  
[www.vefim.it](http://www.vefim.it)  
 Tel. +39 045.820.22.79 - Fax +39 045.827.64.95  
 Ufficio Vendite Italia: venditeitalia@vefim.it